

Backlit

EN Backlit is a professional LED panel luminaire designed for suspended ceiling systems in offices, hotels and commercial interiors. With a white aluminium frame and a standard 595 × 595 mm format, it ensures quick installation, uniform light distribution and high lighting performance. Available in 36W, 40W, and 45W versions, Backlit delivers efficient, comfortable illumination for workspaces and public areas. High-performance LEDs provide wide, even light output, while CRI/Ra >80 supports good colour rendering. With UGR <19, the luminaire helps reduce glare and supports visual comfort in professional office environments.

DE Backlit ist eine professionelle LED-Panelleuchte für abgehängte Deckensysteme in Büros, Hotels und gewerblichen Innenräumen. Mit weißem Aluminiumrahmen und im Standardformat 595 × 595 mm ermöglicht sie eine schnelle Montage, eine gleichmäßige Lichtverteilung und eine hohe Lichtleistung. Erhältlich in 36 W, 40 W und 45 W, bietet Backlit eine effiziente und komfortable Beleuchtung für Arbeits- und öffentliche Bereiche. Leistungsstarke LEDs sorgen für gleichmäßiges Licht, CRI/Ra >80 für eine gute Farbwiedergabe und UGR <19 für hohen Sehkomfort im professionellen Einsatz.

Example

Backlit		standard power		4000 K		microprismatic		no textil
3107	– 00	– 2	– 8	– 4	– 02	– 11	– 1	– 00
	one size		DALI		luminaire white 9010		surface	

Quickinfo

luminaire size		595×595×30
system power	**LO**	30W
	ST	35W
	HI	45W
luminos flux	**LO**	3380lm
	ST	3950lm
	HI	5185lm

Technical information

IP20 · <19 UGR · SDCM 3 · ~230V


luminous efficiency	112lm/W	
light distribution – down	90°	
lighting power	low	~1
	standard	~2
	high	~3
electrical control	ON/OFF	▲9
on request:	on request DALI	▲8
color temperature switchable	3000K	●3
	4000K	●4
luminaire color	white 9010	⬟02
mounting type	surface	◖1
	pendant	◖2

Create my unique code!

3107 – 00 – ~ – ▲ – ● – 02 – 11 – ◖ – 00



JDE BITCREATIVE



light distribution
DOWN

