POWER SWITCHABLE
**25 / 20 / 15 W**

CCT SWITCHABLE
**3000 / 3500 / 4000 K**

ZOOMABLE
**15° to 60°**



# Viva Zoom

**EN** Viva Zoomable is a professional spotlight for three-phase track systems, designed for architectural lighting applications where precision, flexibility and visual comfort are essential. Its sleek, compact cylindrical housing features a clean screwless design with an integrated in-track driver. The luminaire offers switchable technology with selectable power levels 15W/20W/25W and multi-CCT adjustment 3000K/3500K/4000K, allowing one product to meet diverse project requirements. Zoomable optics from 15° to 60° enable smooth adjustment from focused accent lighting to wider illumination. With CRI >90, a flicker-free driver and glare-free optics, Viva Zoomable delivers high-quality light for offices, retail spaces, galleries, showrooms and premium commercial interiors.

**DE** Der Viva Zoomable ist ein professioneller Strahler für Drehstrom-Schienensysteme mit schaltbarer Technologie und wählbaren Leistungsstufen von 15 W, 20 W und 25 W sowie einstellbarer Farbtemperatur (CCT) von 3000 K, 3500 K und 4000 K. Die Zoomoptik mit einem Schwenkbereich von 15° bis 60° ermöglicht eine stufenlose Anpassung von fokussierter Akzentbeleuchtung bis hin zu breiter Ausleuchtung. Mit einem Farbwiedergabeindex (CRI) von über 90, einem flimmerfreien Treiber und einer blendfreien Optik liefert der Viva Zoomable hochwertiges Licht.

## Example

| Viva Zoom | | standard power | | 4000 K | | zoom | | no textil |
|---|---|---|---|---|---|---|---|---|
| 3108 | – 00 – | 2 | – 9 – | 4 | – 01 – | 06 | – 10 – | 00 |
| | one size | | ON/OFF | | luminaire black 9005 | | track light | |

## Quickinfo

| | Viva Zoomable | | |
|---|---|---|---|
| **luminaire size** | Ø 70 × 150 | | |
| **system power** | ↓15 W | ↓20 W | ↓25 W |
| **luminos flux** | 1280 lm | 1700 lm | 2190 lm |
| **luminous efficiency** | 85 lm/W | | |
| **Light distribution – down** | 15° – 60° | | |

## Technical information

IP20 · >90 CRI · <19 UGR · SDCM 3 · ~230V

| | | |
|---|---|---|
| **lighting power** | low | ~ 1 |
| | standard | ~ 2 |
| | high | ~ 3 |
| **mounting type** | track light | |
| **electrical control** | ON / OFF | ▲ 9 |
| on request: | DALI | ▲ 8 |
| **color temperature** | 3000 K | ● 3 |
| | 4000 K | ● 4 |
| on request: | 3500 K | ● 7 |
| **luminaire color** | black 9005 | ⬟ 01 |
| | white 9010 | ⬟ 02 |

**Create my unique code!**

3108 – 00 – ~ – ▲ – ● – ⬟ – 06 – 10 – 00







HERT STUDIO

light distribution DOWN
example for 60°

